

1. Identification

Product identifier: FASLUB® Lubri-10® Penetrating Gel Lubricant
Product code: 611
Recommended use: Lubricant
Restriction on use: For car parts only
Supplier Name: PR Distribution inc.
6500 Rue Zéphirin-Paquet
Québec, Québec
Canada, G2C 0M3
Telephone: 418 872-6018
Emergency tel. number: CHEMTREC 1-800-424-9300 / 1 (703) 527-3887
Available hours: 24/7

2. Hazard identification

Signal word: DANGER

Product classification:



Aerosols - Category 1.

Carcinogenicity - Category 1B. Reproductive toxicity - Category 2. Specific target organ toxicity – repeated exposure - Category 1.

Skin irritation - Category 2. Serious eye irritation - Category 2A. Specific target organ toxicity – single exposure - Category 3 Narcotic effects.

Hazard statement(s):

- H222 - Extremely flammable aerosol.
- H229 - Pressurized container: may burst if heated.
- H350 - May cause cancer.
- H361 - Suspected of damaging fertility or the unborn child.
- H372 - Causes damage to organs (ears, CNS) through prolonged or repeated exposure.
- H315 - Causes skin irritation.
- H319 - Causes serious eye irritation.
- H336 - May cause drowsiness or dizziness.

Precautionary statement(s)

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust and aerosol. Wash hands thoroughly after handling and any other part of the body that may have been exposed to the product. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye and face protection.

Response: IF exposed or concerned: Get medical advice. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Storage: Keep container tightly closed. Store in a well ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 38 °C/100°F.

Disposal: Dispose of contents/container in accordance with local, regional, national and/or international regulations in force.

Other hazards: Moderately toxic by intravenous, intraperitoneal route and subcutaneous routes.

See toxicological information, section 11

3. Composition/ Information on ingredients

No	CAS No :	Common name and synonyms	Concentration % (w/w)
1	67-64-1	Acetone. Dimethyl ketone. 2-propanone	10.00 - 30.00 *
2	64742-47-8	Naphtha hydrotreated, light fraction	10.00 - 30.00 *
3	110-54-3	n-Hexane	5.00 - 10.00 *
4	107-83-5	Iso-Hexane. 2-Methylpentane	7.00
5	79-29-8	2,3-Dimethylbutane	5.00
6	64742-63-8	Distillates (petroleum), solvent-dewaxed heavy naphthenic. Baseoil unspecified	3.00
7	96-14-0	3-Methylpentane	3.00

* The actual concentration range is withheld as a trade secret.

4. First-aid measures

If swallowed, irritation, any type of overexposure or symptoms of overexposure occur during use of the product or persists after use, immediately contact a POISON CENTER, an EMERGENCY ROOM or a PHYSICIAN; ensure that the product safety data sheet is available.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention as soon as possible.

Skin contact: Remove contaminated clothing immediately. Wash the skin with soap and water. Thoroughly wet contaminated clothing. If irritation persists, consult a doctor.

Inhalation: Move exposed person to fresh air. Keep this person warm and lying down. Loosen tight clothing such as a collar, tie, belt or waistband. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention immediately.

Ingestion: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting unless instructed by medical personnel.

Symptoms: Redness, flaking and cracking of the skin. Red eyes, itching, blurred vision and tearing. We can observe headaches, nausea, vomiting and dizziness. Euphoria and desorientation. Possible perceptible deafness, dizziness, tinnitus and hyperacusis.

Effects (acute or delayed): This product is a serious irritant that may cause reversible damages to the cornea. May cause skin irritation. Following repeated or prolonged contact, it has a degreasing effect on the skin. Can cause depression of the central nervous system. May cause peripheral neuropathy. Ototoxic effect after a long-term exposure. Inhalation of high concentrations vapors can cause narcotic effect. Repeated exposure of this product may lead to the development of cancerous tumors.

Immediate medical attention and special treatment: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Suitable extinguishing media: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media: Jets of water can facilitate the spread of fire.

Specific hazards arising from the hazardous product: Flammable. Vapors may form explosive mixtures with air. The vapors are heavier than air and may travel to an ignition source. May release dangerous fumes. Evacuate the area. Fight fire from a safe distance or a protected location. Approach fire from upwind to avoid hazardous vapours or gases.

Hazardous combustion products: Hydrofluoric acid. Carbon monoxide and dioxide.

Special protective equipment and precautions for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions: No action shall be taken involving any personal risk or if you do not have suitable training or protection. Evacuate surrounding areas. Do not touch or walk through spilled material. Shut off all heating and ignition sources. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Protective equipment and emergency procedures: Avoid dispersal of spilled material, runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution. Use inert absorbent or retention tubes in the event of a large spill.

Methods and materials for containment and cleaning up: Stop leak if without risk. Move containers from spill area. Contain leaks and pick up with non-combustible absorbent materials such as sand, earth or vermiculite. Then, place in an appropriate waste disposal container according to local regulations. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Precautions for safe handling: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Avoid contact with eyes, skin and clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Incompatibility: Strong oxidizing agents. Halogenated products. Reductive agents. Oxidizers. Hydrogen peroxide. Amines.

8. Exposure Controls/ Personal protection

Control parameters:

Occupational exposure limit values:

Alberta

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute occupational exposure limit (STEL)		Ceiling occupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	67-64-1	Acetone. Dimethyl ketone. 2-propanone	500	1200	750	1800	Not listed	Not listed
2	64742-47-8	Naphtha hydrotreated, light fraction	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	110-54-3	n-Hexane	50	176	Not listed	Not listed	Not listed	Not listed
4	107-83-5	Iso-Hexane. 2-Methylpentane	500	1760	1000	3500	Not listed	Not listed
5	79-29-8	2,3-Dimethylbutane	500	1760	1000	3500	Not listed	Not listed
6	64742-63-8	Distillates (petroleum), solvent-dewaxed heavy naphthenic. Baseoil unspecified	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
7	96-14-0	3-Methylpentane	500	1760	1000	3500	Not listed	Not listed

British-Columbia

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute occupational exposure limit (STEL)		Ceiling occupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	67-64-1	Acetone. Dimethyl ketone. 2-propanone	250	Not listed	500	Not listed	Not listed	Not listed
2	64742-47-8	Naphtha hydrotreated, light fraction	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	110-54-3	n-Hexane	20	Not listed	Not listed	Not listed	Not listed	Not listed
4	107-83-5	Iso-Hexane. 2-Methylpentane	200	Not listed	Not listed	Not listed	Not listed	Not listed
5	79-29-8	2,3-Dimethylbutane	200	Not listed	Not listed	Not listed	Not listed	Not listed
6	64742-63-8	Distillates (petroleum), solvent-dewaxed heavy naphthenic. Baseoil unspecified	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
7	96-14-0	3-Methylpentane	200	Not listed	Not listed	Not listed	Not listed	Not listed

Ontario

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute occupational exposure limit (STEL)		Ceiling occupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	67-64-1	Acetone. Dimethyl ketone. 2-propanone	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
2	64742-47-8	Naphtha hydrotreated, light fraction	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	110-54-3	n-Hexane	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
4	107-83-5	Iso-Hexane. 2-Methylpentane	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
5	79-29-8	2,3-Dimethylbutane	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
6	64742-63-8	Distillates (petroleum), solvent-dewaxed heavy naphthenic. Baseoil unspecified	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
7	96-14-0	3-Methylpentane	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed

Quebec

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute occupational exposure limit (STEL)		Ceiling occupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	67-64-1	Acetone. Dimethyl ketone. 2-propanone	250	595	500	1190	Not listed	Not listed
2	64742-47-8	Naphtha hydrotreated, light fraction	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	110-54-3	n-Hexane	50, 500 for other isomers	176, 1760 for other isomers	1000 for other isomers	3500 for other isomers	Not listed	Not listed
4	107-83-5	Iso-Hexane. 2-Methylpentane	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
5	79-29-8	2,3-Dimethylbutane	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
6	64742-63-8	Distillates (petroleum), solvent-dewaxed heavy naphthenic. Baseoil unspecified	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
7	96-14-0	3-Methylpentane	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed

Saskatchewan

No	CAS No :	Common name and synonyms	8-hour occupational exposure limit (TWA)		15-minute occupational exposure limit (STEL)		Ceiling occupational exposure limit	
			ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1	67-64-1	Acetone. Dimethyl ketone. 2-propanone	500	Not listed	750	Not listed	Not listed	Not listed
2	64742-47-8	Naphtha hydrotreated, light fraction	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	110-54-3	n-Hexane	50 as n-Hexane, 500 as other isomers	Not listed	62.5 as n-Hexane, 1000 as other isomers	Not listed	Not listed	Not listed
4	107-83-5	Iso-Hexane. 2-Methylpentane	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
5	79-29-8	2,3-Dimethylbutane	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
6	64742-63-8	Distillates (petroleum), solvent-dewaxed heavy naphthenic. Baseoil unspecified	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
7	96-14-0	3-Methylpentane	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed

United States

No	CAS No :	Common name and synonyms	IDLH NIOSH	Regulatory Limits			Recommended Limits	
				OSHA PEL		California / OSHA PEL	NIOSH REL	ACGIH ® 2019 TLV ®
				ppm	mg/m ³	8-hour TWA (ST) STEL (C) Ceiling	Up to 10-hour TWA (ST) STEL (C) Ceiling	8-hour TWA (ST) STEL (C) Ceiling
1	67-64-1	Acetone. Dimethyl ketone. 2-propanone	5938	1000	2400	500 ppm (ST) 750 ppm (C) 3000 ppm	250 ppm	250 ppm (ST) 500 ppm
2	64742-47-8	Naphtha hydrotreated, light fraction	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
3	110-54-3	n-Hexane	3878	500	1800	50 ppm	50 ppm	50 ppm
4	107-83-5	Iso-Hexane. 2-Methylpentane	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
5	79-29-8	2,3-Dimethylbutane	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
6	64742-63-8	Distillates (petroleum), solvent-dewaxed heavy naphthenic. Baseoil unspecified	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed
7	96-14-0	3-Methylpentane	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed

IDLH: Immediately Dangerous to Life or Health Concentrations

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

PEL: Permissible Exposure Limits

California / OSHA: California Division of Occupational Safety and Health

REL: Recommended Exposure Limits

ACGIH ®: American Conference of Governmental Industrial Hygienists

TLV ®: Threshold Limit Values

Appropriate engineering controls: When a worker is exposed to a substance identified as having a demonstrated or suspected carcinogenic, mutagenic and/or reprotoxic effect on humans, exposure must be kept to a minimum, even when it remains within the expected standards regardless of the duration of exposure. Recirculation must be prohibited. Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eyes: DO NOT WEAR CONTACT LENSES. Wear anti-splash safety goggles.

Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties.

Respiratory: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Others: Wear protective clothing with long sleeves and appropriate safety shoes at all times.

9. Physical and chemical properties

Physical state: Aerosol

Colour: Colorless

Odour: Naphtha

Melting/Freezing point: Not applicable, contents under pressure

Initial boiling point/boiling range: Not applicable, contents under pressure

Flammability: Yes

Lower flammable/explosive limit: Not applicable

Upper flammable/explosive limit: Not applicable

Flash point: Not applicable, contents under pressure

Auto-ignition temperature: Not applicable, contents under pressure

Decomposition temperature: Not applicable, contents under pressure

pH: Not applicable

Kinematic viscosity: Not applicable, contents under pressure

Solubility (in water): Insoluble

Partition coefficient – n-octanol/water (Log Kow): Not applicable, contents under pressure

Vapour pressure: Not applicable, contents under pressure

Density and relative density: 0,751 kg/L at 20 °C (water = 1)

Relative vapour density: > 1 (air = 1)

Particle characteristics: Not applicable

10. Stability and reactivity

Reactivity: Stable under recommended conditions of storage and handling.

Chemical stability: The product is chemically stable under normal conditions of use. This product is unstable under the following conditions: The product decomposes when exposed to heat. It has often happened that damaged bottles behave like flares and cause serious damage or injury.

Possibility of hazardous reactions: No dangerous or polymerization reactions will not occur under normal conditions of use. Danger of explosion when heated. Emits toxic fumes when heated. Can generate hydrofluoric acid, a very toxic and corrosive product in contact with water, humidity or an acid.

Conditions to avoid: Avoid electrical discharge. Avoid shock, friction, fire and other sources of ignition. Keep away from sources of ignition, open flames and sparks. Do not pierce or burn, even after use. Keep away from incompatible products (see section 7). Some risk may be expected of corrosive and toxic decomposition products. To avoid thermal decomposition, do not overheat.

Incompatible materials: This product can attack certain types of plastic, rubber or coatings.

Hazardous decomposition products: Carbon monoxide and dioxide. Fluorides.

11. Toxicological information

	Oral	Dermal	Inhalation gases	Inhalation vapours	Inhalation dusts/mists
ATE _{product}	> 5 000 mg/kg	27647.46 mg/kg	N/A	> 20 mg/l	> 5 mg/l

No	CAS No :	Common name and synonyms	LD ₅₀ oral mg/kg	LD ₅₀ skin mg/kg	LC ₅₀ inhalation ppmV 4h - gases	LC ₅₀ inhalation mg/l 4h - vapours	LC ₅₀ inhalation mg/l 4h - dusts-mist
1	67-64-1	Acetone. Dimethyl ketone. 2-propanone	5800	> 15800	N/A	76	> 15.00
2	64742-47-8	Naphtha hydrotreated, light fraction	> 5000	> 5000	N/A	> 20.00	> 5.00
3	107-83-5	Iso-Hexane. 2-Methylpentane	> 5000	> 5000	N/A	> 20.00	> 5.00
4	110-54-3	n-Hexane	28700	3295	N/A	141.00	> 35.00
5	79-29-8	2,3-Dimethylbutane	16750	3350	N/A	> 20.00	259.35
6	64742-63-8	Distillates (petroleum), solvent-dewaxed heavy naphthenic. Baseoil unspecified	> 5000	> 5000	N/A	> 20.00	> 5.00
7	96-14-0	3-Methylpentane	> 5000	> 5000	N/A	> 20.00	> 5.00

Routes of exposure: This product is absorbed through the respiratory tract.

Symptoms: Redness, flaking and cracking of the skin. Red eyes, itching, blurred vision and tearing. We can observe headaches, nausea, vomiting and dizziness. Euphoria and desorientation. Possible perceptive deafness, dizziness, tinnitus and hyperacusis.

Delayed and immediate effects: This product is a serious irritant that may cause reversible damages to the cornea. May cause skin irritation. Following repeated or prolonged contact, it has a degreasing effect on the skin. Can cause depression of the central nervous system. May cause peripheral neuropathy. Ototoxic effect after a long-term exposure. Inhalation of high concentrations vapors can cause narcotic effect. Repeated exposure of this product may lead to the development of cancerous tumors.

Aspiration hazard	N/A
Skin corrosion - Skin irritation	Yes
Serious eye damage - Serious eye irritation - Eye irritation	Yes
Skin sensitization	N/A
Respiratory sensitization	N/A
Specific target organ toxicity – single exposure	N/A
Specific target organ toxicity – single exposure Category 3 Narcotic effects	Yes
Specific target organ toxicity – single exposure Category 3 Respiratory tract irritation	N/A
Specific target organ toxicity – repeated exposure	Yes

No	CAS No :	Common name and synonyms	IARC	ACGIH	Mutagenicity	Effect on reproduction
1	67-64-1	Acetone. Dimethyl ketone. 2-propanone	Not listed	A4	No effects shown.	The data do not allow for an adequate evaluation of the effects on reproduction. The data do not allow for an adequate evaluation of the effects on development.
2	64742-47-8	Naphtha hydrotreated, light fraction	Not listed	Not listed	No effects shown.	No effects shown.
3	107-83-5	Iso-Hexane. 2-Methylpentane	Not listed	Not listed	No effects shown.	No effects shown.
4	110-54-3	n-Hexane	Not listed	Not listed	The data do not allow for an adequate assessment of mutagenic effects.	Possible risk of impaired fertility.
5	79-29-8	2,3-Dimethylbutane	Not listed	Not listed	No effects shown.	No effects shown.
6	64742-63-8	Distillates (petroleum), solvent-dewaxed heavy naphthenic. Baseoil unspecified	Not listed	A1	No effects shown.	No effects shown.
7	96-14-0	3-Methylpentane	Not listed	Not listed	No effects shown.	No effects shown.

Cancer classification under IARC (International Agency for Research on Cancer)

- Group 1: carcinogenic to humans.
- Group 2A: probably carcinogenic to humans.
- Group 2B: possibly carcinogenic to humans.
- Group 3: not classifiable as to its carcinogenicity to humans.
- Group 4: probably not carcinogenic to humans.

Cancer classification under ACGIH (American Conference of Governmental Industrial Hygienists)

- Group A1: confirmed human carcinogen.
- Group A2: suspected human carcinogen.
- Group A3: confirmed animal carcinogen with unknown relevance to humans.
- Group A4: not classifiable as a human carcinogen.
- Group A5: not suspected as a human carcinogen.

12. Ecological information

Ecotoxicity

No	CAS No :	Common name and synonyms	%	Aquatic Ecotoxicity short term	Aquatic Ecotoxicity long term	Terrestrial Ecotoxicity
1	67-64-1	Acetone. Dimethyl ketone. 2-propanone	10.00 - 30.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
2	64742-47-8	Naphtha hydrotreated, light fraction	10.00 - 30.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
3	107-83-5	Iso-Hexane. 2-Methylpentane	7.00	Not available.	Toxic to aquatic life with long lasting effects.	No known adverse effect to the environment.
4	110-54-3	n-Hexane	5.00 - 10.00	Not available.	Toxic to aquatic life with long lasting effects.	No known adverse effect to the environment.
5	79-29-8	2,3-Dimethylbutane	5.00	Not available.	Toxic to aquatic life with long lasting effects.	No known adverse effect to the environment.
6	64742-63-8	Distillates (petroleum), solvent-dewaxed heavy naphthenic. Baseoil unspecified	3.00	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.
7	96-14-0	3-Methylpentane	3.00	Not available.	Toxic to aquatic life with long lasting effects.	No known adverse effect to the environment.

Persistence and degradability. Bioaccumulative potential. Other adverse effects

No	CAS No :	Common name and synonyms	%	Persistent	Bio-accumulation	Aquatic ecotoxicity
1	67-64-1	Acetone. Dimethyl ketone. 2-propanone	10.00 - 30.00	Yes	No	No
2	64742-47-8	Naphtha hydrotreated, light fraction	10.00 - 30.00	No	Yes	Yes
3	107-83-5	Iso-Hexane. 2-Methylpentane	7.00	No	No	Yes
4	110-54-3	n-Hexane	5.00 - 10.00	No	No	Yes
5	79-29-8	2,3-Dimethylbutane	5.00	No	No	No
6	64742-63-8	Distillates (petroleum), solvent-dewaxed heavy naphthenic. Baseoil unspecified	3.00	Yes	Yes	No
7	96-14-0	3-Methylpentane	3.00	No	No	No

Degradability: N/A

Mobility in soil: N/A

13. Disposal considerations

Methods of disposal: The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally.

14. Transport information

	TDG	DOT	IMDG	IATA
UN Number	1950	1950	1950	1950
Proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS
Transport hazard class(es)	2.1	2.1	2.1	2.1
Packing group				

Canada - ERAP

Not applicable

United States - Reportable Quantities (RQ)

No	CAS No :	Common name and synonyms	RQ lbs (kg)
1	67-64-1	Acetone. Dimethyl ketone. 2-propanone	5000 (2270)
2	110-54-3	n-Hexane	5000 (2270)

Transport in bulk (according to Annex II of the International Convention for the Prevention of Pollution From Ships, 1973, as modified by the Protocol of 1978 (MARPOL 73/78), and the International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk (IBC Code)): N/A

Marine pollutant: No

Exemption for limited quantity: 1 L

In accordance with the Canadian Transport of Dangerous Goods regulations by Road, we use the 1.17 exemption when applicable. In accordance with 49 CFR article 172.315 for transportation by a mode other than air, we use the Limited quantities exemption when applicable.

Other exemptions: No other exemption.

Special precautions: Not applicable

15. Regulatory information

Canada

No	CAS No :	Common name and synonyms	%	DSL	NDSL	NPRI
1	67-64-1	Acetone. Dimethyl ketone. 2-propanone	10.00 - 30.00	X		
2	64742-47-8	Naphtha hydrotreated, light fraction	10.00 - 30.00	X		X
3	110-54-3	n-Hexane	5.00 - 10.00	X		X
4	107-83-5	Iso-Hexane. 2-Methylpentane	7.00	X		X
5	79-29-8	2,3-Dimethylbutane	5.00	X		X
6	64742-63-8	Distillates (petroleum), solvent-dewaxed heavy naphthenic. Baseoil unspecified	3.00	X		
7	96-14-0	3-Methylpentane	3.00	X		X

United States

No	CAS No :	Common name and synonyms	%	TSCA	PROP-65	RTK
1	67-64-1	Acetone. Dimethyl ketone. 2-propanone	10.00 - 30.00	X		X
2	64742-47-8	Naphtha hydrotreated, light fraction	10.00 - 30.00	X		
3	110-54-3	n-Hexane	5.00 - 10.00	X	X	X
4	107-83-5	Iso-Hexane. 2-Methylpentane	7.00	X		X
5	79-29-8	2,3-Dimethylbutane	5.00	X		X
6	64742-63-8	Distillates (petroleum), solvent-dewaxed heavy naphthenic. Baseoil unspecified	3.00	X		
7	96-14-0	3-Methylpentane	3.00	X		

The classification of the product and the SDS were developed in accordance with HPR and HazCom 2012.

16. Other information

Date: 2023-11-22

Version: 1

Notice to reader: The manufacturer hereby declares that the information disclosed herein have been based on governmental sites and/or raw material supplier's. The manufacturer has no control over the nature and content of such information. The manufacturer fully reproduces all the information it holds on the constituent of the product, at the time it is manufactured. The manufacturer does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. By this data sheet, the manufacturer hereby discloses all the potential dangers it has knowledge of and which might be related to the using or manipulation of the product in order to allow the proper care to be brought and use with regard to the product. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist and notification is hereby given to the user. Notice is hereby given that injury can derive therefrom if the foregoing is not respected. The manufacturer assumes no responsibility for personal and/or material damage, lost or injury of whichever nature caused or which may occur following the wrongful, inappropriate, negligent or abusive use or handling of the product or from not having read the herein contained information.